Claims

[c1] What is claimed is:

1.A method of routing data between IP-based telephone extensions in a telecommunications network, the telecommunications network comprising: a first Internet Protocol (IP) sharing device for sharing connection to a first IP address:

a first remote telephone group containing a first set of IP-based telephones, the first remote telephone group being connected to the Internet through the first IP sharing device, and each of the IP-based telephones in the first remote telephone groups being assigned a unique identifier;

a second IP sharing device for sharing connection to a second IP address;

a second remote telephone group containing a second set of IP-based telephones, the second remote telephone group being connected to the Internet through the second IP sharing device, and each of the IP-based telephones in the second remote telephone groups being assigned a unique identifier;

a main host connected to the Internet for controlling data traffic over the Internet between the first remote

telephone group and the second remote telephone group; and

a remote host connected to the Internet through the first IP sharing device for linking the first remote telephone group to the second remote telephone group and main host;

the method comprising:

the remote host connecting with and logging into the main host;

generating data packets with a source IP-based telephone in the first remote telephone group for contacting a destination IP-based telephone in the second remote telephone group;

transmitting the data packets to the remote host; the remote host transmitting the data packets to the main host; and

the main host transmitting the data packets to the destination IP-based telephone in the second remote telephone group for establishing communication between the source IP-based telephone in the first remote telephone group and the destination IP-based telephone in the second remote telephone group.

[c2] 2.The method of claim 1 further comprising: generating data packets with a source IP-based telephone in the second remote telephone group for contacting a destination IP-based telephone in the first remote telephone group;

transmitting the data packets to the main host; the main host transmitting the data packets to the remote host; and

the remote host transmitting the data packets to the destination IP-based telephone in the first remote telephone group for establishing communication between the source IP-based telephone in the second remote telephone group and the destination IP-based telephone in the first remote telephone group.

[c3] 3.The method of claim 1 further comprising:
generating data packets with a source IP-based telephone in the first remote telephone group for contacting
a destination IP-based telephone in the first remote telephone group;

the remote host contacting the main host to request connection of the source IP-based telephone and the destination IP-based telephone;

the main host contacting the remote host to grant connection of the source IP-based telephone and the destination IP-based telephone;

the remote host establishing a direct connection between the source IP-based telephone and the destination IP-based telephone; and the source IP-based telephone communicating with the destination IP-based telephone.

- [c4] 4.The method of claim 3 wherein the source IP-based telephone communicates with the destination IP-based telephone locally without connecting to the Internet.
- [c5] 5.The method of claim 1 further comprising:
 terminating connection between the remote host and the
 main host;
 generating data packets with a source IP-based telephone in the first remote telephone group for contacting
 a destination IP-based telephone in the first remote tele-

phone group;

the remote host establishing a direct connection between the source IP-based telephone and the destination
IP-based telephone; and
the source IP-based telephone communicating with the
destination IP-based telephone.

- [c6] 6.The method of claim 5 wherein the source IP-based telephone communicates with the destination IP-based telephone locally without connecting to the Internet.
- [c7] 7.The method of claim 1 wherein the remote host performs bandwidth control functions for the first remote telephone group.

- [08] 8.The method of claim 1 wherein the remote host sends duplicate copies of system information received from the main host to each of the IP-based telephones in the first remote telephone group.
- [09] 9.The method of claim 1 wherein the first and second IP addresses are dynamic IP addresses.
- [c10] 10.A method of routing data between IP-based telephone extensions in a telecommunications network,
 the telecommunications network comprising:
 a first Internet Protocol (IP) sharing device for sharing
 connection to a first IP address;
 a first remote telephone group containing a first set of
 IP-based telephones, the first remote telephone group

IP-based telephones, the first remote telephone group being connected to the Internet through the first IP sharing device, and each of the IP-based telephones in the first remote telephone groups being assigned a unique identifier;

a second IP sharing device for sharing connection to a second IP address;

a second remote telephone group containing a second set of IP-based telephones, the second remote telephone group being connected to the Internet through the second IP sharing device, and each of the IP-based telephones in the second remote telephone groups being

assigned a unique identifier;

a main host connected to the Internet for controlling data traffic over the Internet between the first remote telephone group and the second remote telephone group;

a first remote host connected to the Internet through the first IP sharing device for linking the first remote tele-phone group to the second remote telephone group and main host; and

a second remote host connected to the Internet through the second IP sharing device for linking the second remote telephone group to the first remote telephone group and main host;

the method comprising:

the first and second remote hosts connecting with and logging into the main host;

generating data packets with a source IP-based telephone in the first remote telephone group for contacting a destination IP-based telephone in the second remote telephone group;

transmitting the data packets to the first remote host; the first remote host transmitting the data packets to the second remote host; and

the second remote host transmitting the data packets to the destination IP-based telephone in the second remote telephone group for establishing communication between the source IP-based telephone in the first remote telephone group and the destination IP-based telephone in the second remote telephone group.

[c11] 11.The method of claim 10 further comprising:
generating data packets with a source IP-based telephone in the second remote telephone group for contacting a destination IP-based telephone in the first remote telephone group;
transmitting the data packets to the second remote host;
the second remote host transmitting the data packets to
the first remote host; and
the first remote host transmitting the data packets to the
destination IP-based telephone in the first remote telephone group for establishing communication between
the source IP-based telephone in the second remote
telephone group and the destination IP-based telephone

[c12] 12.The method of claim 10 further comprising:
generating data packets with a source IP-based telephone in the first remote telephone group for contacting
a destination IP-based telephone in the first remote telephone group;

in the first remote telephone group.

the first remote host contacting the main host to request connection of the source IP-based telephone and the destination IP-based telephone; the main host contacting the first remote host to grant connection of the source IP-based telephone and the destination IP-based telephone;

the first remote host establishing a direct connection between the source IP-based telephone and the destination IP-based telephone; and

the source IP-based telephone communicating with the destination IP-based telephone.

- [c13] 13.The method of claim 12 wherein the source IP-based telephone communicates with the destination IP-based telephone locally without connecting to the Internet.
- [c14] 14.The method of claim 10 further comprising: terminating connection between the first remote host and the main host;

generating data packets with a source IP-based telephone in the first remote telephone group for contacting a destination IP-based telephone in the first remote telephone group;

the first remote host establishing a direct connection between the source IP-based telephone and the destination IP-based telephone; and

the source IP-based telephone communicating with the destination IP-based telephone.

[c15] 15.The method of claim 14 wherein the source IP-based

- telephone communicates with the destination IP-based telephone locally without connecting to the Internet.
- [c16] 16.The method of claim 10 wherein the first and second remote hosts perform bandwidth control functions for the first and second remote telephone groups, respectively.
- [c17] 17. The method of claim 10 wherein the first and second remote hosts send duplicate copies of system information received from the main host to each of the IP-based telephones in the first and second remote telephone groups, respectively.
- [c18] 18. The method of claim 10 wherein the first and second IP addresses are dynamic IP addresses.